



DESCRIPTION

FROSTOX® R is an engine cooling system cleaner with surfactants for internal combustion engines. It easily removes oily contaminants from the cooling system. **FROSTOX® R** contains high-quality corrosion inhibitors and safely protect all the various metals used in engines. **FROSTOX® R** is suitable for use with cast iron and all-aluminium engines.

OEM APPROVALS

FROSTOX® R is approved by the following manufacturers:

Audi: VW G05218801 Skoda: VW G05218801
 Seat: VW G05218801 Volkswagen: VW G05218801

PHYSICAL AND CHEMICAL PROPERTIES





	Value	Method
Density at 20°C [g/cm³]	1.025–1.045	DIN 51757
Refractive index	1.370–1.382	DIN 53423
pH value (33 % aqueous solution)	9.0–9.8	ASTM D1287

PERFORMANCE CHARACTERISTICS

FROSTOX® R can be mixed even with hard water in any concentration with no precipitate formation. **FROSTOX® R** is mixed with water in a 1:1 ratio and added to the cooling system which, after the thermostat has opened, is then cleaned for approximately 10 minutes with the engine running (at operating temperature). Next, the liquid is drained and the system flushed with water. If the cooling system is heavily contaminated, the procedure should be repeated.

CONTAINER AND DELIVERY SPECIFICATIONS

FROSTOX® R is dyed a reddish purple. The following container sizes are available:

	1		1.5 litre			3		5		10		20		30 litre
	60		200 litre			20 to 24 tons								

Please inquire for additional container sizes if required.