

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Frostox® SF-D12DI++

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	26.04.2019	4226706-00001	Date of first issue: 26.04.2019

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Frostox® SF-D12DI++  
Product code : 10107

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Corrosion inhibitor  
stance/Mixture

#### 1.3 Details of the supplier of the safety data sheet

Company : HAERTOL Chemie GmbH  
Havelstr. 21  
39126 Magdeburg  
Telephone : +49 391 2800 231  
Telefax : +49 391 2800 280  
E-mail address of person : info@haertol.de  
responsible for the SDS

#### 1.4 Emergency telephone number

+49 6132 / 84463

---

### SECTION 2: Hazards identification


#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms : 

Signal word : Warning

Hazard statements : H302 Harmful if swallowed.  
H373 May cause damage to organs through prolonged or

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Frostox® SF-D12DI++

Version 1.0      Revision Date: 26.04.2019      SDS Number: 4226706-00001      Date of last issue: -  
Date of first issue: 26.04.2019

repeated exposure.

Precautionary statements :

### Prevention:

P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.

### Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.  
P314 Get medical advice/ attention if you feel unwell.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

Ethylene glycol

### Additional Labelling

EUH205 Contains epoxy constituents. May produce an allergic reaction.

### 2.3 Other hazards

None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Ethylene glycol	107-21-1 203-473-3 603-027-00-1	Acute Tox. 4; H302 STOT RE 2; H373	>= 90 - <= 100
2-Ethylhexanoic acid	149-57-5 205-743-6 607-230-00-6	Repr. 2; H361d	>= 1 - < 3

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Frostox® SF-D12DI++

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	26.04.2019	4226706-00001	Date of first issue: 26.04.2019

---

- when the potential for exposure exists.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Harmful if swallowed.  
May cause damage to organs through prolonged or repeated exposure.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

- Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Nitrogen oxides (NO<sub>x</sub>)

### 5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Frostox® SF-D12DI++

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	26.04.2019	4226706-00001	Date of first issue: 26.04.2019

---

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

#### 6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Frostox® SF-D12DI++

Version 1.0      Revision Date: 26.04.2019      SDS Number: 4226706-00001      Date of last issue: -  
Date of first issue: 26.04.2019

- Advice on safe handling : Avoid inhalation of vapour or mist.  
Do not swallow.  
Avoid contact with eyes.  
Avoid prolonged or repeated contact with skin.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.
- Advice on common storage : Do not store with the following product types:  
Strong oxidizing agents
- Storage class (TRGS 510) : 10, Combustible liquids
- Storage period : 60 Months
- Recommended storage temperature : > -25 °C

### 7.3 Specific end use(s)

- Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Ethylene glycol	107-21-1	TWA	20 ppm 52 mg/m <sup>3</sup>	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	40 ppm 104 mg/m <sup>3</sup>	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		AGW (Vapour and aerosols)	10 ppm 26 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	2;(I)			
Further information	Senate commission for the review of compounds at the work place dangerous			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Frostox® SF-D12DI++

Version 1.0      Revision Date: 26.04.2019      SDS Number: 4226706-00001      Date of last issue: -  
Date of first issue: 26.04.2019

	for the health (MAK-commission)., European Union (The EU has established a limit value: deviations in value and peak limit are possible), Sum of vapor and aerosols., Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
2,2',2''-Nitrilotriethanol	102-71-6	AGW (Inhalable fraction)	1 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	1;(I)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Ethylene glycol	Workers	Inhalation	Long-term local effects	35 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	106 mg/kg bw/day
	Consumers	Inhalation	Long-term local effects	7 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	53 mg/kg bw/day
2-Ethylhexanoic acid	Workers	Inhalation	Long-term systemic effects	14 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	3,5 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	1 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1 mg/kg bw/day
	2,2',2''-Nitrilotriethanol	Workers	Skin contact	Long-term systemic effects
	Workers	Inhalation	Long-term local effects	5 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	5 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	13 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	3,1 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	1,25 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	1,25 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Ethylene glycol	Fresh water	10 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Frostox® SF-D12DI++

Version 1.0      Revision Date: 26.04.2019      SDS Number: 4226706-00001      Date of last issue: -  
Date of first issue: 26.04.2019

	Marine water	1 mg/l
	Intermittent use/release	10 mg/l
	Sewage treatment plant	199,5 mg/l
	Fresh water sediment	37 mg/kg
	Marine sediment	3,7 mg/kg
	Soil	1,53 mg/kg
2-Ethylhexanoic acid	Fresh water	0,36 mg/l
	Marine water	0,036 mg/l
	Intermittent use/release	0,493 mg/l
	Sewage treatment plant	71,7 mg/l
	Fresh water sediment	6,37 mg/kg
	Marine sediment	0,637 mg/kg
	Soil	1,06 mg/kg
2,2',2''-Nitrilotriethanol	Fresh water	0,32 mg/l
	Marine water	0,032 mg/l
	Intermittent use/release	5,12 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	1,7 mg/kg dry weight (d.w.)
	Marine sediment	0,17 mg/kg dry weight (d.w.)
	Soil	0,151 mg/kg dry weight (d.w.)
Sebacic acid	Fresh water	0,018 mg/l
	Marine water	0,0018 mg/l
	Intermittent use/release	0,18 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	0,547 mg/kg
	Marine sediment	0,0547 mg/kg
	Soil	0,0986 mg/kg dry weight (d.w.)

### 8.2 Exposure controls

#### Engineering measures

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

#### Personal protective equipment

Eye protection : Wear the following personal protective equipment:  
Safety glasses  
Equipment should conform to DIN EN 166

#### Hand protection

Material : butyl-rubber  
Break through time : > 30 min  
Glove thickness : 0,7 mm  
Directive : DIN EN 374  
Protective index : Class 2

Material : Nitrile rubber  
Break through time : > 30 min  
Glove thickness : 0,4 mm  
Directive : DIN EN 374

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Frostox® SF-D12DI++

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	26.04.2019	4226706-00001	Date of first issue: 26.04.2019

---

Protective index	:	Class 2
Remarks	:	Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
Skin and body protection	:	Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Filter type	:	Organic vapour type (A)

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	customer specific
Odour	:	characteristic
Odour Threshold	:	No data available
pH	:	8,1 (20 °C)
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	> 170 °C
Flash point	:	> 110 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Frostox® SF-D12DI++

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	26.04.2019	4226706-00001	Date of first issue: 26.04.2019

---

Vapour pressure	:	ca. 0,2 hPa (20 °C)
Relative vapour density	:	No data available
Density	:	1,115 g/cm <sup>3</sup> (20 °C)
Solubility(ies)		
Water solubility	:	completely miscible
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

### 9.2 Other information

Flammability (liquids)	:	No data available
Particle size	:	Not applicable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Can react with strong oxidizing agents.
---------------------	---	-----------------------------------------

### 10.4 Conditions to avoid

Conditions to avoid	:	None known.
---------------------	---	-------------

### 10.5 Incompatible materials

Materials to avoid	:	Oxidizing agents
--------------------	---	------------------

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Frostox® SF-D12DI++

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	26.04.2019	4226706-00001	Date of first issue: 26.04.2019

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation  
Skin contact  
Ingestion  
Eye contact

##### Acute toxicity

Harmful if swallowed.

##### Product:

Acute oral toxicity : Acute toxicity estimate: 544,96 mg/kg  
Method: Calculation method

##### Components:

##### Ethylene glycol:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg  
Method: Expert judgement

Acute inhalation toxicity : LC50 (Rat): > 2,5 mg/l  
Exposure time: 6 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Mouse): > 3.500 mg/kg

##### 2-Ethylhexanoic acid:

Acute oral toxicity : LD50 (Rat): 2.043 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

##### Skin corrosion/irritation

Not classified based on available information.

##### Components:

##### Ethylene glycol:

Species : Rabbit  
Result : No skin irritation

##### 2-Ethylhexanoic acid:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Frostox® SF-D12DI++

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	26.04.2019	4226706-00001	Date of first issue: 26.04.2019

---

### Serious eye damage/eye irritation

Not classified based on available information.

#### Components:

##### Ethylene glycol:

Species	:	Rabbit
Result	:	No eye irritation

##### 2-Ethylhexanoic acid:

Species	:	Rabbit
Method	:	OECD Test Guideline 405
Result	:	No eye irritation

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Components:

##### Ethylene glycol:

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Result	:	negative

##### 2-Ethylhexanoic acid:

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Result	:	negative

### Germ cell mutagenicity

Not classified based on available information.

#### Components:

##### Ethylene glycol:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
-----------------------	---	-----------------------------------------------------------------------------------------------------------

##### 2-Ethylhexanoic acid:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
-----------------------	---	------------------------------------------------------------------------

Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
----------------------	---	--------------------------------------------------------------------------------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Frostox® SF-D12DI++

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	26.04.2019	4226706-00001	Date of first issue: 26.04.2019

---

Species: Mouse  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative

### **Carcinogenicity**

Not classified based on available information.

### **Components:**

#### **Ethylene glycol:**

Species : Mouse  
Application Route : Ingestion  
Exposure time : 2 Years  
Result : negative

### **Reproductive toxicity**

Not classified based on available information.

### **Components:**

#### **2-Ethylhexanoic acid:**

Effects on fertility : Test Type: Fertility/early embryonic development  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

### **STOT - single exposure**

Not classified based on available information.

### **STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

### **Components:**

#### **Ethylene glycol:**

Exposure routes : Ingestion  
Target Organs : Kidney  
Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Frostox® SF-D12DI++

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	26.04.2019	4226706-00001	Date of first issue: 26.04.2019

---

### Repeated dose toxicity

#### Components:

##### Ethylene glycol:

Species	: Rat
NOAEL	: 150 mg/kg
Application Route	: Ingestion
Exposure time	: 2 yr

Species	: Dog
NOAEL	: 2.200 - 4.400 mg/kg
Application Route	: Skin contact
Exposure time	: 4 Weeks
Method	: OECD Test Guideline 410

##### 2-Ethylhexanoic acid:

Species	: Rat
NOAEL	: 300 mg/kg
Application Route	: Ingestion
Exposure time	: 91 - 93 Days

### Aspiration toxicity

Not classified based on available information.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### Ethylene glycol:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 72.860 mg/l Exposure time: 96 h
------------------	-----------------------------------------------------------------------------------

Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
-----------------------------------------------------	-----------------------------------------------------------------------------------------------------------

Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapitata (green algae)): 6.500 - 13.000 mg/l Exposure time: 96 h
----------------------------------	----------------------------------------------------------------------------------------------------

Toxicity to fish (Chronic toxicity)	: NOEC: 15.380 mg/l Exposure time: 7 d Species: Pimephales promelas (fathead minnow)
-------------------------------------	--------------------------------------------------------------------------------------------

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 8.590 mg/l Exposure time: 7 d Species: Ceriodaphnia dubia (water flea)
------------------------------------------------------------------------	--------------------------------------------------------------------------------------

##### 2-Ethylhexanoic acid:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Frostox® SF-D12DI++

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	26.04.2019	4226706-00001	Date of first issue: 26.04.2019

---

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 180 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 106 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): 49,3 mg/l Exposure time: 72 h
Toxicity to microorganisms	:	EC50 (Pseudomonas putida): 112,1 mg/l Exposure time: 17 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 25 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

### 12.2 Persistence and degradability

#### Components:

##### **Ethylene glycol:**

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 90 - 100 % Exposure time: 10 d Method: OECD Test Guideline 301A
------------------	---	-------------------------------------------------------------------------------------------------------------------------

##### **2-Ethylhexanoic acid:**

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 99 % Exposure time: 28 d Method: OECD Test Guideline 301E
------------------	---	-------------------------------------------------------------------------------------------------------------------

### 12.3 Bioaccumulative potential

#### Components:

##### **Ethylene glycol:**

Bioaccumulation	:	Species: Leuciscus idus (Golden orfe) Bioconcentration factor (BCF): 10
-----------------	---	----------------------------------------------------------------------------

Partition coefficient: n-octanol/water	:	log Pow: -1,93
----------------------------------------	---	----------------

##### **2-Ethylhexanoic acid:**

Partition coefficient: n-octanol/water	:	log Pow: 2,7
----------------------------------------	---	--------------

### 12.4 Mobility in soil

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Frostox® SF-D12DI++

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	26.04.2019	4226706-00001	Date of first issue: 26.04.2019

---

### 12.5 Results of PBT and vPvB assessment

Not relevant

### 12.6 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

- Product : Dispose of in accordance with local regulations.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.
- 

## SECTION 14: Transport information

### 14.1 UN number

Not regulated as a dangerous good

### 14.2 UN proper shipping name

Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

### 14.4 Packing group

Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Frostox® SF-D12DI++

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	26.04.2019	4226706-00001	Date of first issue: 26.04.2019

---

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EC) No 850/2004 on persistent organic pollutants	:	Not applicable
Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals	:	Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 3
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.		Not applicable
Water contaminating class (Germany)	:	WGK 1 slightly hazardous to water Classification according to AwSV, Annex 1 (5.2)

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

---

### SECTION 16: Other information

Other information	:	Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.
-------------------	---	--------------------------------------------------------------------------------------------------------------------------------

#### Full text of H-Statements

H302	:	Harmful if swallowed.
H361d	:	Suspected of damaging the unborn child.
H373	:	May cause damage to organs through prolonged or repeated exposure if swallowed.

#### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Repr.	:	Reproductive toxicity
STOT RE	:	Specific target organ toxicity - repeated exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Frostox® SF-D12DI++

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	26.04.2019	4226706-00001	Date of first issue: 26.04.2019

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Acute Tox. 4	H302
STOT RE 2	H373

### Classification procedure:

Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Frostox® SF-D12DI++

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	26.04.2019	4226706-00001	Date of first issue: 26.04.2019

---

intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN